

Overview

Novra is pleased to introduce the S300CA into our lineup of DVB-based IP/MPEG receiver/routers. Based on Novra's latest generation hardware platform, the enhanced features of the S300CA extend your DVB-S2 performance by expanding operation down to 100 Ksps and up to 32 APSK; by increasing data throughput to 80 Mbps; and by handling complex multi-stream VCM signals with embedded Input Stream Identifier (ISI) filtering.



The S300CA is designed for use as a video streaming streaming appliance for encrypted programming. It provides a user-friendly graphical user interface, that only requires the selection of the desired program (from the displayed Program Listing) and the destination IP address/port. The S300CA provides the flexibility to choose which Audio and Teletext PID's to be included with the stream, and will re-generate the PAT to support Single Program Transport Streams (SPTS) or Multi-Program Transport Streams (MPTS).

The inclusion of a Common Interface (CI) slot in the S300CA provides a cost effective means to provide compatibility with the vast majority of currently available DVB conditional access systems.

Applications

The S300CA is ideally suited for small-medium enterprise/consumer use, delivering IP or MPEG applications that require encrypted security measures or providing aggregation/distribution of encrypted MPEG-2 programming. Typical applications include: IPTV content aggregation (head end) and/or delivery, hotel or cruise ship infotainment, distance education, digital signage, corporate LAN's and cable network head-ends.

Features

- DVB-S/DVB-S2 Compliant
 - Multi-stream VCM Operation with ISI Filtering
 - 32 APSK Operation
 - Downloadable Firmware
 - Support for Gold Code Sequences
 - 80 Mbps Sustained Throughput
 - RJ45 10/100 Base-T Ethernet Interface
 - Exceptional Flexibility - Delivery of IP or MPEG Services
- MPEG Features
 - Full Transponder Program Listing
 - User-Friendly Program-Based Configuration
 - Selectable Audio or Teletext PID pass-through
 - Selectable SI Table PID pass-through
 - Single Program PAT Re-generation
 - SPTS/MPTS
 - Multicast full DVB Multiplex onto LAN

Technical Specifications: Novra S300CA Receiver/Router

RF Tuners

- Receiving Frequency: 950 to 2150 MHz
- Frequency Acquisition: ± 10 MHz above 10 Msps
- Input Signal Level: -70 dBm to -25 dBm

Multi-standard Demodulation

- QPSK: 100 Ksps to 45 Msps (DVB-S)
- QPSK: 100 Ksps to 45 Msps (DVB-S2)
- 8PSK: 100 Ksps to 45 Msps (DVB-S2)
- 32APSK: 100 Ksps to 45 Msps (DVB-S2)
- Automatic Symbol Rate detection and lock
- Automatic Code Rate detection and lock
- Data Throughput: 80 Mbps
- Nyquist Root Filter: 0.2, 0.25, 0.35 rolloff
- Multi-stream VCM
- ISI Filteirng
- ACM Support

Multi-Standard Decoding FEC

DVB-S

- Viterbi 1/2, 2/3, 3/4, 5/6, 6/7, 7/8 puncture rates
- Reed Soliman 16 bit decoder

DVB-S2

- LDPC 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 rates
- BCH (Bose-Chaudhuri-Hocquenghem) decoder

Gold Code Sequencing

- 0 to 262143 sequences

LNB Power and Control

- LNB Supply Voltage: Selectable 11/15V, 13/18V, 21V or off
- LNB Supply with selectable long line compensation
- LNB Control: Selectable 22 KHz, 44 KHz, or off
- LNB Supply Current: 400 mA with Short Circuit and Surge Protection

Configuration

- IP Address Configuration
- PID/Program Selection
- LNB Power
- Transponder Settings
- Management Console Application available as an MS Windows Executable
- Command Line tool available for Linux, Windows, MAC OS, and FreeBSD

Status Monitoring

- Signal Strength
- Signal Lock, Data Lock
- Error status: C/N Viterbi BER, Uncorrectable Errors

Status Indicators

- Power: Red LED
- Lock: Blue LED
- Data: Blue LED
- Ethernet Link (green) and Transmit (yellow)

Hardware Capabilities

- Multiprotocol Encapsulation (MPE)
- PID Filters: 32
- Simultaneous MPEG Programs: 16
- Internal Hardware Watchdog
- Non-Volatile Configuration Storage
- Field upgradable operating system for new s/w releases and functional upgrades

Operating Systems

- Once Configured, receiver supports all OS's

Physical Interfaces

- RF Input Connector: F-Type, 75 ohms
- Ethernet 10/100 Base-T LAN Interface: RJ-45
- CI Slot: PCMCIA

Physical/Environmental

- Height: 1.41 in (3.58 cm)
- Width: 5.22 in (13.26 cm)
- Depth: 4.10 in (10.42 cm)
- Weight: 1 lbs (0.46 Kg)
- Operating Temperature: 0C to 40C
- Storage Temperature: -55C to 85C
- Operating Humidity: 10 to 90% Non-Condensing

Standards/Regulatory

- UDP/IP Protocol
- IP Multicast
- IGMP: V1.0, V2.0
- ETSI 301.192 DVB
- ISO/IEC 13818-1
- ISO/IEC 13818-6
- IEEE 802.3 10/100 Mbps
- FCC/Industry Canada
- EN 55022 (Emission)/EN 55024 (Immunity)
- Safety EN 60950

Other S300 Models

- S300D DVB-S2 IP Receiver
- S300V: DVB-S2 IP/MPEG Receiver
- 1RU mounting option for up to three S300CA's.

