



Overview

Novra is pleased to introduce the S300D into our lineup of DVB-based IP data receiver/routers.

Based on Novra's latest generation hardware platform, the enhanced features of the S300D extend your DVB-S2 performance by expanding operation down to 100 Ksps and up to 32 APSK; by increasing data throughput to 80 Mbps; and by handling complex multi-stream VCM signals with embedded Input Stream Identifier (ISI) filtering.

The S300D lets you choose your demodulation technique, supporting QPSK, 8PSK, and 32 APSK over a variety of coding rates. Compatibility with the DVB-S2 standard enables you to take advantage of the significant efficiency gains when compared with DVB-S.

Installation of the S300D is easy and noninvasive, as the client does not need to be opened, nor are any drivers required. The S300D works with any OS and makes the received IP data available to any client on the LAN.

Applications

The S300D is perfectly suited for a range of small-medium enterprise/consumer applications including the reception of IP-based services with the flexibility of Variable or Constant Coding/Modulation.

Applications include: weather imaging and data, distance education, digital signage, data content distribution, streaming content, Internet over satellite, and IPTV content distribution to single or multiple viewers.

Features

- DVB-S2/DVB-S Compliant, including
 - Multistream VCM Operation with ISI Filtering
 - 32 APSK Operation
- 80 Mbps Sustained Throughput
- Support for ACM operation
- Support for Gold Code Sequences
- Downloadable Firmware
- RJ45 10/100BaseT Ethernet Interface
- Application Transparent
- Small Footprint
- IGMP Filtering



Technical Specifications: Novra S300D Receiver/Router

RF Tuners

- Receiving Frequency: 950 to 2150 MHz
- Frequency Acquisition: ± 10 MHz above 10 Msps
- Input Signal Level: -70 dBm to -25 dBm

Multi-standard Demodulation

- QPSK: 100 Ksps to 45 Msps (DVB-S)
- QPSK: 100 Ksps to 45 Msps (DVB-S2)
- 8PSK: 100 Ksps to 45 Msps (DVB-S2)
- 32 APSK: 100 Ksps to 45 Msps (DVB-S2)
- Automatic Symbol Rate detection and lock
- Automatic Code Rate detection and lock
- Data Throughput: 80 Mbps
- Nyquist Root Filter: 0.2, 0.25, 0.35 rolloff
- Multi-stream VCM
- ISI Filteirng
- ACM Support

Multi-Standard Decoding FEC

DVB-S

- Viterbi 1/2, 2/3, 3/4, 5/6, 6/7, 7/8 puncture rates
- Reed Soliman 16 bit decoder

DVB-S2

- LDPC 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 rates
- BCH (Bose-Chaudhuri-Hocquenghem) decoder

Gold Code Sequencing

- 0 to 262143 sequences

LNB Power and Control

- LNB Supply Voltage: Selectable 11/15V, 13/18V, 21V or off

- LNB Supply with selectable long line compensation

- LNB Control: Selectable 22 KHz, 44 KHz, or off
- LNB Supply Current: 400 mA with Short Circvuit and Surge Protection

Configuration

- IP Address Configuration
- PID Selection
- LNB Power
- Transponder Settings
- Management Console Application available as an MS Windows Executable
- Command Line tool available for Linux, Windows, MAC OS, and FreeBSD

- Signal Strength
- Signal Lock, Data Lock
- Error status: C/N Viterbi BER, Uncorrectable Errors

Status Indicators

- Power: Red LED
- Lock: Blue LED
- Data: Blue LED
- Ethernet Link (green) and Transmit (yellow)

Hardware Capabilities

- Multiprotocol Encapsulation (MPE)
- PID Filters: 32
- Internal Hardware Watchdog
- Non-Volatile Configuration Storage
- Field upgradable operating system for new s/w releases and functional upgrades

Operating Systems

- Once Configured, receiver supports all OS's

Physical Interfaces

- RF Input Connector: F-Type, 75 ohms
- Ethernet 10/100 Base-T LAN Interface: RJ-45

Physical/Environmental

- Height: 1.41 in (3.58 cm)
- Width: 5.22 in (13.26 cm)
- Depth: 4.10 in (10.42 cm)
- Weight: 1 lbs (0.46 Kg)
- Operating Temperature: 0C to 40C
- Storage Temperature: -55C to 85C
- Operating Humidity: 10 to 90% Non-Condensing

Standards/Regulatory

- UDP/IP Protocol
- IP Multicast
- IGMP: V1.0, V2.0
- ETSI 301.192 DVB
- ISO/IEC 13818-1
- ISO/IEC 13818-6
- IEEE 802.3 10/100 Mbps
- FCC/Industry Canada
- EN 55022 (Emission)/EN 55024 (Immunity)
- Safety EN 60950

Other S300 Models

- S300V: DVB-S2 IP/MPEG Receiver/Router
- S300CA: DVB-S2 IP/MPEG Receiver/Router with CI Slot
- 1RU mounting option for up to three S300D's.



Status Monitoring